

2011



XTRIM™ COMMANDER™ LIMITED 600 E-TEC

ENGINE

Platform	LXU
Engine Rotax	600 H.O. E-TEC
Engine Type	Reed valve, 3D R.A.V.E.
Number of cylinder	2
Displacement, cm³	594,4
Bore, mm	72
Stroke, mm	73
Power, kW	85
Max Power at RPM	8000
Fuel System	Electronic DI
Type of Lubrication	Electr. Oil pump
Type of Cooling	Liquid
Starter	EI + Rewind starter
Electric start	STD

TRANSMISSION

Drive pulley	TRA 3
Driven pulley	QRS
Chain	Syncro
Gearing	1: 3,23 - 2: 1,98 / 8

SUSPENSION

Front Suspension Type	A-LFS
Front Shocks	HPG 36
Suspension Travel, front mm	210
Rear Suspension Type	RCG-A
Rear / Center Shock	HPG 36 / HPG 36
Suspension Travel, rear mm	340

WEIGHTS / TRACK / CAPACITIES

Dryweight, Kg	287
Width, mm	1120-1162
Length, mm	3230
Height mm	1330
Ski Stance, mm	975 adj. (+42mm)
Track Width, mm	500
Track Length, mm	3923
Track Profile Height, mm	38
Fuel Tank, liters	45
Oil Tank, liters	2,8

MATERIALS

Hood, material	Polyamidi
Bottom Pan, material	Polypropylene
Skis	CTRL II with carbide
Chassis, Material	Aluminium

STANDARD EQUIPMENTS/ACCESSORIES

DESS	STD
Electric Power Outlet	STD
Fuel gauge	Electric
Handlebars	Steel J-hook bar with riser block & mountain strap
Handle Heater	STD
Heated Passenger Handles	ACCESSORY
Hitch	Hook type
Passenger Seat Backrest	STD
Extra Passenger Seat	STD
Rear Mirror	ACCESSORY
Reverse Type	Mechanical (2F N R) Syncro
Speedometer	STD
Storage Rack	STD
Skid plate	ACCESSORY
Tachometer	STD
Temperature gauge	STD
Windshield	High
Air Deflector	-



**BEAT THE EXTREME
CONDITIONS**

LYNX®

