# **SKANDIC** WT



EN		NIE.	CIL		CE
-1					
	-		$\sim$ 1 1	$\sim$	$\sim$

Engine	Rotax 600 ACE	Rotax E-TEC® 600 H.O.	
Engine details	Liquid-cooled, four-stroke	Liquid-cooled,	
	D.O.H.C., dry sump	3-D R.A.V.E.™	
Cylinders	2	2	
Displacement	600 cc / 36.6 in <sup>3</sup>	594.4 cc / 36.3 in <sup>3</sup>	
Bore	74 mm / 2.9 in	72 mm / 2.8 in	
Stroke	69.7 mm / 2.7 in	73 mm / 2.9 in	
Maximum engine speed	7250 RPM	8100 RPM	
Carburation	EFI	Electronic Direct Injection	
Recommended fuel type	Regular unleaded	Premium unleaded	
Minimum octane	87	91	
Fuel tank	45 liters / 12 gallons	45 liters / 12 gallons	
Oil tank capacity	2.1 liters / 2.3 quarts	3.7 liters / 3.9 quarts	
Exhaust system	Double head-pipe, baffle muffler	Single tuned-pipe, rear entry, baffle muffler	

### **POWERTRAIN**

Drive clutch type	eDrive™	TRA™ III
Driven clutch type	QRS	QRS
Engagement	2200 RPM	3000 RPM
Small sprocket number of teeth	1 <sup>st</sup> gear = 3.23:1 ratio	1st gear = 3.23:1 ratio
Large sprocket number of teeth	$2^{\text{nd}}$ gear = 1.98:1 ratio	$2^{nd}$ gear = 1.98:1 ratio
Drive sprocket number of teeth	8	8
Drive sprocket diameter	183 mm / 7.2 in	183 mm / 7.2 in
Brake system	Hydraulic	Hydraulic
DRY WEIGHT	278 kg / 613 lb	282 kg / 622 lb

## PACKAGE HIGHLIGHTS

- NEW REV-XU<sup>™</sup> Platform
- NEW Skandic body with full coverage bumper
- **NEW** SC<sup>™</sup>-5U articulating rear suspension
- 20 x 154 x 1.5-inch track
- Lynx Telescopic front suspension
- Pilot<sup>™</sup> 6.9 skis
- Synchromesh transmission with reverse (2-1-N-R)
- Electric start
- Analog gauge with display
- High windshield with mirrors
- Mountain strap
- Air radiator with fan
- 12V power outlet
- 2-up seat with passenger handholds
- Cargo rack
- Hitch

## **EXTRA HIGHLIGHTS** 600 ACE

- NEW Rotax® 600 ACE (Advanced Combustion Efficiency) engine with 650W of magneto power
- Engine oil cooler

## **COLOR CHOICE**

Yel	low	/ R	lack

#### **DIMENSIONS**

Vehicle overall length	3240 mm / 127.5 in	
Vehicle overall width	1076mm / 42.4 in	
Vehicle overall height	1330 mm / 52.3 in	
Ski stance	900 mm / 35.4 in	
Ski overall length	1066 mm / 42 in	
Ski width	175 mm / 6.9 in	
Track nominal width	508 mm / 20 in	
Track nominal length	3923 mm / 154 in	
Track profile height	38.1 mm / 1.5 in	

# **SUSPENSION**

Front suspension	LTS
Front shock	Motion Control
Front suspension max. travel	150 mm / 6 in
Rear suspension	SC-5U
Center shock	Motion Control
Rear shock	HPG
Rear suspension max. travel	340 mm / 13.4 in

#### **FEATURES**

Frame	REV-XU	Reverse	Mechanical	Fuel gauge	Standard
Skis	Pilot 6.9	Heated throttle lever	Standard	Mirrors	Standard
Seating	2-up modular with underseat storage	Heated grips	Standard	Windshield	515 mm / 20 ir
Backrest	Standard	Speedometer	Standard	Carbide runner	Standard
Handlebar	Painted steel with J-hooks / Mountain strap	Tachometer	Standard	Hitch	Tongue type
Electric start	Standard				

