

2011 SKANDIC® TUNDRA™ LT



PACKAGE HIGHLIGHTS

- REV-XU™ platform
- SC™-5U articulating rear suspension
- 16 x 154 x 1.5-inch track
- Lynx Telescopic front suspension
- Pilot™ 6.9 skis
- Electric start
- Analog gauge with display
- **NEW** REV-XP™ 2-up seat with strap
- 480-mm / 19-inch windshield
- Mountain strap
- Cargo rack
- HPG™ rear shock
- Hitch

EXTRA HIGHLIGHTS

600 ACE

- **NEW** Rotax® 600 ACE (Advanced Combustion Efficiency) engine with 650W of magneto power
- High windshield
- Engine oil cooler
- Air radiator with fan

550F

- RER™ electronic reverse
- **NEW** Low oil light

COLOR CHOICE

Yellow / Black

DIMENSIONS

Vehicle overall length	3329 mm / 131.6 in
Vehicle overall width	1002 mm / 39.4 in
Vehicle overall height	1325 mm / 52.2 in
Ski stance	813 mm / 32 in
Ski overall length	1066 mm / 42 in
Ski width	175 mm / 6.9 in
Track nominal width	406 mm / 16 in
Track nominal length	3923 mm / 154 in
Track profile height	38.1 mm / 1.5 in

SUSPENSION

Front suspension	LTS
Front shock	Motion Control
Front suspension max. travel	150 mm / 6 in
Rear suspension	SC-5U
Center shock	Motion Control
Rear shock	HPG
Rear suspension max. travel	340 mm / 13.4 in

ENGINE CHOICE

Engine	Rotax 600 ACE	Rotax 550F
Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump	Axial fan-cooled, cylinder reed porting
Cylinders	2	2
Displacement	600 cc / 36.6 in³	553.4 cc / 33.8 in³
Bore	74 mm / 2.9 in	76 mm / 3 in
Stroke	69.7 mm / 2.7 in	61 mm / 2.4 in
Maximum engine speed	7250 RPM	6800 RPM
Carburation	EFI	2X VM-30
Recommended fuel type	Regular unleaded	Regular unleaded
Minimum octane	87	87
Fuel tank	40 liters / 10.6 gallons	40 liters / 10.6 gallons
Oil tank capacity	2.1 litres / 2.3 quarts	3.7 liters / 3.9 quarts
Exhaust system	Double head-pipe, baffle muffler	Single tuned-pipe, baffle muffler

POWERTRAIN

Drive clutch type	eDrive™	TRA™ III
Driven clutch type	QRS	LPV
Engagement	2200 RPM	2400 RPM
Small sprocket number of teeth	21	19
Large sprocket number of teeth	51	45
Drive sprocket number of teeth	8	8
Drive sprocket diameter	183 mm / 7.2 in	183 mm / 7.2 in
Brake system	Hydraulic	Hydraulic

DRY WEIGHT

229 kg / 505 lb 219 kg / 483 lb

FEATURES

Frame	REV-XU	Reverse	Mechanical RER (550F)	Fuel gauge	Standard
Skis	Pilot 6.9			Mirrors	Optional
Seating	2-up with strap	Heated throttle lever	Standard	Windshield	480 mm / 19 in
Handlebar	Painted steel with J-hooks / Mountain strap	Heated grips	Standard	Carbide runner	Standard
Riser block height	205 mm / 8 in	Speedometer	Standard	Hitch	Tongue type
Electric start	Standard	Tachometer	Standard		

